Convolutional Neural Network Exercises

1. Counting Parameters

Consider a convolutional neural network that is used to classify images into ten classes. The following table describes the structure of the network. Complete the table with the number of trainable parameters associated with each layer. All convolutions are padded to retain the image dimensions. Assume that each convolutional filter and each dense unite has a single bias weight.

Layer Number	Layer Properties	Parameter Count
Layer 0	32x32 3-channel color images	0
Layer 1	Convolutional layer with 40 3x3 filters	
Layer 2	Convolutional layer with 40 3x3 filters	
Layer 3	Max Pooling layer with stride 2 and 2x2 pooling size	
Layer 4	Convolutional layer with 64 3x3 filters	
Layer 5	Convolutional layer with 64 3x3 filters	
Layer 6	Dense layer with 128 units	
Layer 7	Dense output layer with 10 units	
		TOTAL:

2. Convolutional Networks in Keras

Using cifar_challenge.py as a starting point, implement a neural network classifier that conforms to the structure described above. The printout from model.summary() should allow you to check your parameter counts.

- (a) What is the maximum validation performance that you see when you run this model? Is it better than your earlier results using a non-convolutional network?
- (b) After how many epochs does the model start to overfit the training data?
- (c) Dry adding Dropout layers to see if you can improve your validation performance.
- (d) (Optional) Try using keras's ImageDataGenerator to train your model using input data augmentation.