

CS240

Nathan Sprague

September 3, 2021

A Complication

- Let's analyze this algorithm:

```
1 public static boolean contains(int target,
2                               int[] numbers) {
3     for (int number : numbers) {
4         if (number == target) {
5             return true;
6         }
7     }
8     return false;
9 }
```

Best, Worst, Average Case

```
1 public static boolean contains(int target,
2                               int[] numbers) {
3     for (int number : numbers) {
4         if (number == target) {
5             return true;
6         }
7     }
8     return false;
9 }
```

- Best Case: 1 comparison, $O(1)$
- Worst Case: n comparisons, $O(n)$
- Average Case: $\frac{n+1}{2}$ comparisons, $O(n)$

Refined Algorithm Analysis Algorithm

- STEP 1: Decide on best, worst, or average case analysis
- STEP 2: Select a measure of input size and a basic operation
- STEP 3: Find a function $T(n)$ that describes the number of times the basic operation occurs
- STEP 4: Describe $T(n)$ using order notation:
 - Big-O for an upper bound
“The algorithm is at least this fast!”
 - Big- Ω for a lower bound
“The algorithm is at least this slow!”
 - Big- Θ for both upper and lower bound

L'Hôpital's Rule

L'Hôpital's Rule

If $\lim_{n \rightarrow \infty} f(n) = \lim_{n \rightarrow \infty} g(n) = \infty$ and $f'(n)$ and $g'(n)$ exist, then

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = \lim_{n \rightarrow \infty} \frac{f'(n)}{g'(n)}$$

L'Hôpital Example

- $n \log_2 n \stackrel{?}{\in} O(n^2)$

L'Hôpital Example

- $n \log_2 n \stackrel{?}{\in} O(n^2)$
- $\lim_{n \rightarrow \infty} \frac{n \log_2 n}{n^2} = \lim_{n \rightarrow \infty} \frac{\log_2 n}{n}$

L'Hôpital Example

- $n \log_2 n \stackrel{?}{\in} O(n^2)$
- $\lim_{n \rightarrow \infty} \frac{n \log_2 n}{n^2} = \lim_{n \rightarrow \infty} \frac{\log_2 n}{n}$
- $= \lim_{n \rightarrow \infty} \frac{\ln n}{n \ln 2}$ (Recall that $\log_b(n) = \frac{\log_k n}{\log_k b}$)

L'Hôpital Example

- $n \log_2 n \stackrel{?}{\in} O(n^2)$
- $\lim_{n \rightarrow \infty} \frac{n \log_2 n}{n^2} = \lim_{n \rightarrow \infty} \frac{\log_2 n}{n}$
- $= \lim_{n \rightarrow \infty} \frac{\ln n}{n \ln 2}$ (Recall that $\log_b(n) = \frac{\log_k n}{\log_k b}$)
- Apply L'Hôpital's rule:
- $= \lim_{n \rightarrow \infty} \frac{\frac{1}{n}}{\ln 2}$ (Recall that $\frac{d}{dx} \ln x = 1/x$)

L'Hôpital Example

- $n \log_2 n \stackrel{?}{\in} O(n^2)$
- $\lim_{n \rightarrow \infty} \frac{n \log_2 n}{n^2} = \lim_{n \rightarrow \infty} \frac{\log_2 n}{n}$
- $= \lim_{n \rightarrow \infty} \frac{\ln n}{n \ln 2}$ (Recall that $\log_b(n) = \frac{\log_k n}{\log_k b}$)
- Apply L'Hôpital's rule:
- $= \lim_{n \rightarrow \infty} \frac{\frac{1}{n}}{\ln 2}$ (Recall that $\frac{d}{dx} \ln x = 1/x$)
- $= \lim_{n \rightarrow \infty} \frac{1}{n \ln 2} = 0$

What If We Want to Show That $f(n)$ is NOT $O(g(n))$

- Easiest approach is usually to show:

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = \infty$$

OpenDSA Question

Suppose that a particular algorithm has time complexity $T(n) = 3 \times 2^n$ and that executing an implementation of it on a particular machine takes t seconds for n inputs. Now suppose that we are presented with a machine that is 64 times as fast. How many inputs could we process on the new machine in t seconds?

OpenDSA Question

- Let's call the input size we could handle before n_{old} . The number of steps we completed in t seconds was: $3 \times 2^{n_{old}}$.
- Since our new computer is 64 times faster, the number of steps we can perform in t seconds is now $64 \times 3 \times 2^{n_{old}}$
- Our complexity function tells us that $steps = 3 \times 2^n$, we can solve for size (n):
- $s = 3 \times 2^n$
- $s/3 = 2^n$
- $\log_2(s/3) = n$
- $n = \log_2(s/3)$

OpenDSA Question

Now we plug in our step budget for s :

- $n = \log_2\left(\frac{64 \times 3 \times 2^{n_{old}}}{3}\right)$

- $n = \log_2(64 \times 2^{n_{old}})$

- $n = \log_2(2^6 \times 2^{n_{old}})$

- $n = \log_2(2^{n_{old}+6})$

- $n = n_{old} + 6$