## CS444 Numpy Exercises

1. Download the file numpy\_exercises.py. At the top of the main method instantiate numpy arrays representing each of the following:

$$B = \begin{bmatrix} 1 & 2 & -3 \\ 3 & 4 & -1 \end{bmatrix}, A = \begin{bmatrix} 2 & -5 & 1 \\ 1 & 4 & 5 \\ 2 & -1 & 6 \end{bmatrix}, y = \begin{bmatrix} 2 \\ -4 \\ 1 \end{bmatrix}, z = \begin{bmatrix} -15 \\ -8 \\ -22 \end{bmatrix}$$

provide numpy code that calculates and prints each of the quantities below.

- BA
- $\bullet$   $AB^T$
- Ay
- $y^Tz$  (This is the inner product, or dot product, of y and z.)
- $yz^T$  (This is the outer product of y and z.)
- 2. Complete the function solve\_for\_x(A, z) so that it matches the documentation. Test your function by un-commenting the appropriate lines in main. (The command for matrix inverse in numpy is np.linalg.inv().)
- 3. Complete the functions print\_rows and print\_cols. each method should use array slicing to print each row (or column) to a separate line. Test your functions by uncommenting the appropriate lines in main.
- 4. Complete the function squared\_error(X, w, y). This function should return the quantity:

$$\sum_{\mathbf{x}_i \in \mathbf{X}} (\mathbf{x}_i \mathbf{w}^T - y_i)^2$$

Add code to your main to test the completed function.

5. If you have time: add a new method with the signature squared\_error\_fast(X, w, y). This method should compute the same value as squared\_error, but it should do so without using any loops.

1